

**Glydea™, the difference is in the details**  
The sophistication of Glydea™ is reflected in the simple form and sleek lines of the motor and the rail.

**Aesthetic**

- Patented cover design conceals unsightly cables and protects the connectors and control modules inside the motor.
- Automatic or adjustable limit setting.
- Rail design and swivel ceiling bracket minimize the light gap.
- Soft start and soft stop.
- Back release function and rail design promote optimal stacking of drapery fabric (available with Glydea™ 35)

**Flexible**

- Patented flexible master carrier reduces friction and is adaptable to various drapery types.

**Easy Installation**

- Spring loaded one-touch hardware
- Motor can also be installed to the right or to the left side of the track.
- Standard or inverse motor mounting available

**Quiet**

- Motor design and the use of a timing belt provides quiet operation (<44dBA)

**Efficient**

- Touch Motion feature allows the user to activate the motorized drapery simply by pulling on the fabric (available with Glydea™ 60e)
- Manual override disengages the motor when drapery is adjusted manually. This is ideal for power outages and also protects the fabric from damage.
- My Function allows user to set a preferred drapery openness position for easy access.
- Adjustable speed: 12.5cm/s to 20cm/s


**Glydea™, Somfy quality**

5 year international warranty. International certifications.

## Adaptable and Universal

- With one rail, two motors and various control modules, Glydea™ offers a wide range of options for any project requirement.
- Rail up to 36 ft. (10.9m) wide with Glydea™ 60e and up to 30 ft. (9m) with Glydea™ 35
- Available with custom bends and curves
- Wide variety of hardware and accessories for various drapery types including Pinch Pleat, RippleFold® and Accordia®

Motor Dimensions  
Glydea™ 35 and Glydea™ 60e



## Features overview

	Glydea™ 35	Glydea™ 60e
<b>Motor unit main features</b>		
Soft start	✓	✓
Manual operation	✓	✓
Automatic limits on end stop	✓	✓
Back Release	✓	✓
Soft stop	✓	✓
Intermediate position	✓	✓
Touch motion	✓	✓
Adjustable limits	✓	✓
Speed control & adjustment	✓	✓
<b>Control options</b>		
3 normally open dry contacts	✓	✓
2 normally open dry contacts	✓	✓
2 normally open dry contact sequencing mode	✓	✓
Dry contact individual and group & master control	✓	✓
Tandem	✓	✓
RS485 digital technology	✓	✓
Radio Technology Somfy® RTS	✓	✓
ZigBee®	✓	✓
Z-Wave®	✓	✓
Sun control	✓	✓
Timer control	✓	✓
Infrared	✓	✓
<b>Installation and setting features</b>		
Setting with buttons on motor unit	✓	✓
Setting with external 3 normally open dry contact switch	✓	✓
LED indicators	✓	✓
Motor unit direction change	✓	✓
Factory reset	✓	✓
Inverse mounting	✓	✓
<b>Tracks / Draperies types</b>		
Side opening	✓	✓
Center opening	✓	✓
Asymmetric	✓	✓
Multiple	✓	✓
Pinch pleat	✓	✓
RippleFold® with overlap arm	✓	✓
RippleFold® with butt arm	✓	✓
Accordia®	✓	✓

## Motorized track main characteristics

	Glydea™ 35	Glydea™ 60e
Power supply	120 V	
Amperage	0.5 A	1A
Average linear speed	20 cm/s	12.5 cm/s to 20 cm/s
Power consumption	60 W	120 W
Power cable type	3-wire cable	3-wire cable
Control connector type	RJ12	RJ12
DCT control circuit voltage	3.3 VDC	3.3 VDC
Motorized track noise level	< 50 dB(A)	< 44 dB(A)*
Certifications	c TUV us, CCC, CE	
Track maximum length	30 ft (9 m)	36 ft (10.9 m)
Maximum number of junctions	2	
Minimum bending radius	11.8 in. (30 cm)	
Minimum curving radius	11.8 in. (30 cm)	
Side opening max weight	77 lbs./30 ft 35 kg./9 m	132 lbs./36 ft 58 kg./10.9 m
Center opening max weight	77 lbs./30 ft 35 kg./9 m	132 lbs./36 ft 58 kg./10.9 m
Tandem max weight	Contact Somfy	

## Other available rail shapes

